

Declaration of Performance No. 5156 - 001

- | | |
|---|---|
| 1. Product Type | Bugle Head, Fine Thread, Drywall Screws |
| 2. Type and Batch | Drywall screws are identified by the Batch No. on a label attached to the box or other packaging. |
| 3. Intended Use | Mechanical fasteners for gypsum plasterboard systems |
| 4. Manufacturer | Hexstone Ltd t/a Owlett-Jaton, Opal Way, Stone ST15 0SW
Factory 495 and 546 |
| 5. Authorised Representative | N/A |
| 6. System of Assessment | System 4 |
| 7. Technical Assessment and Notified Bodies | Tested to EN 14566:2008+A1:2009.
N/A |
| 8. D o P for ETA | N/A |
| 9. Declaration of Performance | |

	Criteria	3.5mm	4.2mm	4.8mm
Length	L +/- 1.5mm	Pass	Pass	Pass
Withdrawal force	450N min	Pass	Pass	Pass
Tested in metal section (0.60±0.04)mm thick to EN 14195 and timber member 50mm x 50mm (fastener perpendicular to the grain) conforming to EN 338 class C16 having 15(±3)% moisture content				
Bending behaviour	10° without cracking	Pass	Pass	Pass
Drilling performance	1 sec max	Pass	Pass	Pass
Coating thickness (Zinc and Yellow)	5µm, min	Pass	Pass	Pass
Coating (Black Phosphate)	48hrs, no visible rust	Pass	Pass	Pass
Case hardness at 0.05mm depth	55HRC, min	Pass	Pass	Pass
Material used for production		C1018	C1018	C1018
Class of corrosion protection	48hrs, no visible rust	Pass	Pass	Pass
Reaction to fire		A1		


The previous performance relates to the following product range

Diameter	3.5mm	4.2mm	4.8mm	
Length	25			
	32			
	35			
	38			
	42			
	45			
	50			
	55			
	60			
			65	
			75	
			100	100

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9

The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed on behalf of the manufacturer

Name and Function	Place and Date	Signature
Nick Horton	Stone	
Purchasing Director	5/6/18	